


2025 TERYX KRX® 4 1000

Kawasaki
Let the Good Times Roll®



TERYX KRX 4 1000
TERYX KRX 4 1000
TERYX KRX® 4 1000
TERYX KRX 4 1000
TERYX KRX 4 1000

SMOKY GRAY/SUPER BLACK 

POTENCIA

Motor	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled
Cilindrada	999cc
Potencia máxima	110.0 hp ¹ @ 8,500 rpm
Par máximo	75.2 lb-ft @ 7,000 rpm
Diámetro x Carrera	92.0 x 75.1mm
Relación de compresión	11.5:1
Sistema de combustible	DFI® with (2) 50mm throttle bodies
Ignition	TCBI with electronic advance
Arranque	Electric
Transmisión	Automatic CVT with centrifugal clutch (H,L,N,R)
Transmisión final	Selectable 2WD/4WD with locking front differential, shaft
Freno motor	Yes

CAPACIDAD

Suspensión delantera/ recorrido del neumático	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in
Suspensión trasera/ recorrido del neumático	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in
Neumáticos delanteros	Maxxis® Carnivore 31 x 10.00R15 8PR
Neumáticos traseros	Maxxis® Carnivore 31 x 10.00R15 8PR
Wheel Type	Llantas de aleación con beadlock
Dirección	Electric Power Steering (EPS) / rack-and-pinion
Freno delantero	258mm dual hydraulic discs with 2-piston calipers
Freno trasero	258mm dual hydraulic discs with single-piston calipers
Altura libre al suelo	14.4 in (max), 14.0 in (std)

Capacidad de combustible	10.6 gal
Radio de giro	20.3 ft
Dimensiones del compartimento de carga (LxAxA)	14.6 x 33.1 x 9.1 in
Capacidad de carga del compartimento de carga	351 lb
Capacidad de carga útil	781 lb
Capacidad de asientos	2
Capacidad de remolque	N/A
Luces	(2) LED headlights, (2) LED taillights, LED stoplight

DETALLES

Cuadro	Ladder type, tubular steel
Longitud total	132.1 in
Anchura total	68.1 in
Altura total	77.0 in
Peso en seco	1,839.0 lb** / 1,841.2 lb** CA Model
Peso en orden de marcha	1,938.2 lb* / 1,940.4 lb* CA Model
Distancia entre ejes	98.8 in
Instrumentación	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Características adicionales	KQR™ Sport Roof, Front Bumper, Steel skid-plates w/ drain holes, TFT Full-Color Instrumentation with Smartphone Connectivity
Opciones de color	Sky Blue/Super Black
Garantía	Garantía limitada de 6 meses



KAWASAKI SE PREOCUPA: Lea el Manual de usuario y todas las advertencias del producto. Lleve siempre puesto un casco protección para los ojos, y ropa adecuada. Nunca conduzca bajo la influencia de las drogas o el alcohol. Cumpla con el programa de mantenimiento en su manual del propietario. ©2025 Kawasaki Motors Corp., U.S.A. Especificaciones sujetas a cambios.



RECOMIENDA

